

Model: AGB4573ZTZ
Product Description

Type: Reciprocating Compressors
Application: HBP - High Back Pressure
Refrigerant: R-404A
Voltage/Frequency: 440V 3~ 60Hz 400V 3~ 50Hz
Version: N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	(E) W/W					
EN12900	440V 3~ 60HZ	68553	17275	20086	7831	8.75	2.21	2.56	5°C (41°F)	45°C (113°F)	32°C (90°F)	15°C (59°F)	45°C (113°F)
EN12900	400V 3~ 50HZ	57130	14397	16739	6526	8.75	2.21	2.56	5°C (41°F)	45°C (113°F)	32°C (90°F)	15°C (59°F)	45°C (113°F)

General

Evaporating Temp. Range: -6.7°C to 12.8°C (20°F to 55°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 49
Weight Unit of Measure: KG
Displacement (cc): 135
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 1960

Electrical

Voltage Range (50 Hz): 340-440
Voltage Range (60 Hz): 396-499
Locked Rotor Amps (LRA): 61
Rated Load Amps (RLA 50 Hz): 10.7
Rated Load Amps (RLA 60 Hz): 13.4
Max. Continuous Current (MCC in Amps): 0

Motor Resistance (Ohm) - Main:	2.2
Motor Resistance (Ohm) - Start:	2.2
MotorType:	3PH
Overload Type:	
Relay Type:	

Agency Approval

CCC Listed, CE Listed, GOST RUSSIA Listed, GOST UKRAINE Listed, IRAM Listed, SASO Listed, UL Recognized, cURus Recognized