

Model: AHC2490ZHZ
Product Description

Type: Reciprocating Compressors
Application: LBP - Low Back Pressure
Refrigerant: R-404A
Voltage/Frequency: 208-220V ~ 60Hz
Version: N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
EN12900	220V ~ 60HZ	4802	1210	1407	1915	2.51	.63	.73	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	-25°C (-13°F)	40°C (104°F)

General

Evaporating Temp. Range: -40°C to -12.2°C (-40°F to 10°F)
Motor Torque:
Compressor Cooling:

Mechanical

Weight: 38
Weight Unit of Measure: KG
Displacement (cc): 74.25
Oil Type:
Viscosity (cSt):
Oil Charge (cc): 0

Electrical

Voltage Range (50 Hz):
Voltage Range (60 Hz):
Locked Rotor Amps (LRA): 0
Rated Load Amps (RLA 50 Hz): 0
Rated Load Amps (RLA 60 Hz): 12
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: .5

Motor Resistance (Ohm) - Start: 2.55
MotorType:

Overload Type:

Relay Type:

Agency Approval

CE Listed, SASO Listed, UL Recognized, cURus Recognized