

Model: AE2413Y-FZ1A
Product Description

Type: Reciprocating Compressors
Application: LBP - Low Back Pressure
Refrigerant: R-134a
Voltage/Frequency: 220-240V ~ 50Hz
Version: N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
ASHRAE (R-134a)	220V ~ 50HZ	1100	277	322	265	4.15	1.05	1.22	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)	32°C (90°F)
ASHRAE (R-513A)	220V ~ 50HZ	1297	327	380	310	4.18	1.05	1.23	-23°C (-10°F)	54°C (130°F)	32°C (90°F)	32°C (90°F)	32°C (90°F)

General

Evaporating Temp. Range: -40°C to -10°C (-40°F to 14°F)
Motor Torque: High Start Torque (HST)
Compressor Cooling: Fan

Mechanical

Weight: 0
Weight Unit of Measure: KG
Displacement (cc): 12.01
Oil Type: Polyolester
Viscosity (cSt): 32
Oil Charge (cc): 387

Electrical

Voltage Range (50 Hz): 198-253
Voltage Range (60 Hz):
Locked Rotor Amps (LRA): 12
Rated Load Amps (RLA 50 Hz): 1.77
Rated Load Amps (RLA 60 Hz): 0
Max. Continuous Current (MCC in Amps): 0
Motor Resistance (Ohm) - Main: 8.23
Motor Resistance (Ohm) - Start: 13.41
Motor Type: CSIR
Overload Type:
Relay Type:

Agency Approval

CE Listed, IRAM Listed, VDE Listed