

Model: AGB2513ZKZ
Product Description

Type:	Reciprocating Compressors
Application:	LBP - Low Back Pressure
Refrigerant:	R-404A
Voltage/Frequency:	220V 3~ 60Hz 220V 3~ 50Hz
Version:	N/A


Product Specifications
Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
EN12900	220V 3~ 50HZ	6218	1567	1822	2290	2.72	.68	.8	-35°C (-31°F)	40°C (104°F)	32°C (90°F)	-25°C (-13°F)	40°C (104°F)

General

Evaporating Temp. Range:	-40°C to -12.2°C (-40°F to 10°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	46
Weight Unit of Measure:	KG
Displacement (cc):	112.5
Oil Type:	Polyolester
Viscosity (cSt):	32
Oil Charge (cc):	1960

Electrical

Voltage Range (50 Hz):	180-253
Voltage Range (60 Hz):	187-264
Locked Rotor Amps (LRA):	86
Rated Load Amps (RLA 50 Hz):	8.7
Rated Load Amps (RLA 60 Hz):	9.4
Max. Continuous Current (MCC in Amps):	0
Motor Resistance (Ohm) - Main:	1

Motor Resistance (Ohm) - Start: 1
Motor Type: 3PH

Overload Type:

Relay Type:

Agency Approval

CE Listed, GOST RUSSIA Listed, GOST UKRAINE Listed, SASO Listed, UL Recognized, cURus Recognized