

**Model: AGB4553ZTZ**
**Product Description**

**Type:** Reciprocating Compressors  
**Application:** HBP - High Back Pressure  
**Refrigerant:** R-404A  
**Voltage/Frequency:** 440V 3~ 60Hz 400V 3~ 50Hz  
**Version:** N/A


**Product Specifications**
**Performance**

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
EN12900	440V 3~ 60HZ	50195	12649	14707	5865	8.56	2.16	2.51	5°C (41°F)	45°C (113°F)	32°C (90°F)	15°C (59°F)	45°C (113°F)
EN12900	400V 3~ 50HZ	41761	10524	12236	4576	9.13	2.3	2.67	5°C (41°F)	45°C (113°F)	32°C (90°F)	15°C (59°F)	45°C (113°F)

**General**

**Evaporating Temp. Range:** -6.7°C to 12.8°C (20°F to 55°F)  
**Motor Torque:** High Start Torque (HST)  
**Compressor Cooling:** Fan

**Mechanical**

**Weight:** 46  
**Weight Unit of Measure:** KG  
**Displacement (cc):** 100.7  
**Oil Type:** Polyolester  
**Viscosity (cSt):** 32  
**Oil Charge (cc):** 1960

**Electrical**

**Voltage Range (50 Hz):** 340-440  
**Voltage Range (60 Hz):** 396-499  
**Locked Rotor Amps (LRA):** 45  
**Rated Load Amps (RLA 50 Hz):** 7.9  
**Rated Load Amps (RLA 60 Hz):** 8.4  
**Max. Continuous Current (MCC in Amps):** 0

Motor Resistance (Ohm) - Main:  
Motor Resistance (Ohm) - Start:

Motor Type: 3PH

Overload Type:

Relay Type:

## Agency Approval

CE Listed, GOST RUSSIA Listed, GOST UKRAINE Listed, IRAM Listed, SASO Listed, UL Recognized, VDE Listed, cURus Recognized