

Model: RK5512Y-NA3A

Product Description

Type:	Rotary Compressors
Application:	HBP/AC - Air Conditioning
Refrigerant:	R-134a
Voltage/Frequency:	208-220V ~ 60Hz
Version:	N/A



Product Specifications

Performance

Condition	Test Voltage	Refrigeration Capacity			Input Power (I) W	(E) Efficiency			EVAP TEMP	Condition	AMBIENT TEMP	RETURN GAS	LIQUID TEMP
		(R) Btu/h	(R) kcal/h	(R) W		(E) Btu/Wh	(E) kcal/Wh	W/W					
ASHRAE (R-134a)	230V ~ 60HZ	11900	2999	3487	1123	10.6	2.67	3.1	7.2°C (45°F)	54°C (130°F)	35°C (95°F)	35°C (95°F)	46°C (115°F)

General

Evaporating Temp. Range:	-15°C to 15°C (5°F to 59°F)
Motor Torque:	High Start Torque (HST)
Compressor Cooling:	Fan

Mechanical

Weight:	33
Weight Unit of Measure:	LB
Displacement (cc):	23.9
Oil Type:	Polyolester
Viscosity (cSt):	
Oil Charge (cc):	540

Electrical

Voltage Range (50 Hz):	
Voltage Range (60 Hz):	187-254
Locked Rotor Amps (LRA):	30
Rated Load Amps (RLA 50 Hz):	0
Rated Load Amps (RLA 60 Hz):	5
Max. Continuous Current (MCC in Amps):	0
Motor Resistance (Ohm) - Main:	2.05

Motor Resistance (Ohm) - Start:
Motor Type:

2.92
PSC

Overload Type:

Relay Type:

Agency Approval

cURus Recognized